

NPM SSL Unrecognized Certificate APIs v1.0

Copyright © Riverbed Technology Inc. 2024

Created Jan 16, 2024 at 02:01 PM

Resource: ignored_cert

This resource deals with an unrecognized ignored certificate

http://{device}/api/npm.unrecognized_certs/1.0/ignored_certs/items/{id}

JSON

```
{
  "host_name": string,
  "id": string,
  "ip_addr": string,
  "port": integer
}
```

Property Name	Type	Description	Notes
<i>ignored_cert</i>	<object>	This resource deals with an unrecognized ignored certificate	
<i>ignored_cert.host_name</i>	<string>	The Hostname of the server which sent the certificate	Optional;
<i>ignored_cert.id</i>	<string>	A unique id for the certificate	Optional;
<i>ignored_cert.ip_addr</i>	<string>	The IP address of the server which sent the certificate	Optional;
<i>ignored_cert.port</i>	<integer>	The port of the server which sent the certificate	Optional;

Links

ignored_cert: delete

DELETE http://{device}/api/npm.unrecognized_certs/1.0/ignored_certs/items/{id}

Response Body

On success, the server does not provide any body in the responses.

Resource: ignored_certs

This resource deals with unrecognized ignored certificates

http://{device}/api/npm.unrecognized_certs/1.0/ignored_certs

JSON

```
{
  "items": [ ignored_cert ],
  <prop>: any
}
```

Property Name	Type	Description	Notes
<i>ignored_certs</i>	<object>	This resource deals with unrecognized ignored certificates	
<i>ignored_certs.items</i>	<array of <ignored_cert>>		Optional;
<i>ignored_certs.items[items]</i>	<ignored_cert>	This resource deals with an unrecognized ignored certificate	
<i>ignored_certs.<prop></i>	<any>		Optional;

Links

ignored_certs: bulk_create

Adds to the list of unrecognized ignored certificates

POST http://{device}/api/npm.unrecognized_certs/1.0/ignored_certs/bulk_create

Request Body

Provide an [ignored_certs](#) data object.

Response Body

Returns an [ignored_certs](#) data object.

ignored_certs: bulk_delete

Deletes from the list of unrecognized ignored certificates

```
POST http://{device}/api/npm.unrecognized_certs/1.0/ignored_certs/bulk_delete
```

Request Body

Provide a [certs_bulk_deleter](#) data object.

Response Body

Returns a [certs_bulk_deleter](#) data object.

ignored_certs: create

```
POST http://{device}/api/npm.unrecognized_certs/1.0/ignored_certs
```

Request Body

Provide an [ignored_cert](#) data object.

Response Body

Returns an [ignored_cert](#) data object.

ignored_certs: get

Returns the list of unrecognized ignored certificates

```
GET http://{device}/api/npm.unrecognized_certs/1.0/ignored_certs
```

Response Body

Returns an [ignored_certs](#) data object.

ignored_certs: reset

Resets the list of unrecognized ignored certificates

```
POST http://{device}/api/npm.unrecognized_certs/1.0/ignored_certs/reset
```

Request Body

Do not provide a request body.

Response Body

On success, the server does not provide any body in the responses.

Resource: recent_certs

This resource deals with unrecognized recent certificates

```
http://{device}/api/npm.unrecognized_certs/1.0/recent_certs
```

JSON

```

{
  "items": [
    {
      "appearance_count": integer,
      "details": string,
      "first_seen": integer,
      "host_name": string,
      "id": string,
      "ip_addr": string,
      "last_seen": integer,
      "port": integer
    }
  ],
  <prop>: any
}

```

Property Name	Type	Description	Notes
<i>recent_certs</i>	<object>	This resource deals with unrecognized recent certificates	
<i>recent_certs.items</i>	<array of <object>>		Optional;
<i>recent_certs.items[items]</i>	<object>	An unrecognized recent certificate	
<i>recent_certs.items[items].appearance_count</i>	<integer>	Number of time this certificate appeared on the wire	Optional;
<i>recent_certs.items[items].details</i>	<string>	Details about this certificate	Optional;
<i>recent_certs.items[items].first_seen</i>	<integer>	Time (seconds from epoch) at which this certificate was first seen	Optional;
<i>recent_certs.items[items].host_name</i>	<string>	The Hostname of the server which sent the certificate	Optional;
<i>recent_certs.items[items].id</i>	<string>	A unique id for the certificate	Optional;
<i>recent_certs.items[items].ip_addr</i>	<string>	The IP address of the server which sent the certificate	Optional;
<i>recent_certs.items[items].last_seen</i>	<integer>	Time (seconds from epoch) at which this certificate was last seen	Optional;
<i>recent_certs.items[items].port</i>	<integer>	The port of the server which sent the certificate	Optional;
<i>recent_certs.<prop></i>	<any>		Optional;

Links

recent_certs: get

Returns the list of unrecognized recent certificates

```
GET http://{device}/api/npm.unrecognized_certs/1.0/recent_certs
```

Response Body

Returns a [recent_certs](#) data object.

recent_certs: reset

Resets the list of unrecognized recent certificates

```
POST http://{device}/api/npm.unrecognized_certs/1.0/recent_certs/reset
```

Request Body

Do not provide a request body.

Response Body

On success, the server does not provide any body in the responses.

Type: certs_bulk_deleter

used for doing bulk deletes

JSON

```

{
  "delete_all": boolean,
  "delete_ids": [
    string
  ],
  <prop>: any
}

```

Property Name	Type	Description	Notes
<i>certs_bulk_deleter</i>	<i><object></i>	used for doing bulk deletes	
<i>certs_bulk_deleter.delete_all</i>	<i><boolean></i>	delete all objects in the given config	Optional;
<i>certs_bulk_deleter.delete_ids</i>	<i><array of <string>></i>		Optional;
<i>certs_bulk_deleter.delete_ids[items]</i>	<i><string></i>		
<i>certs_bulk_deleter.<prop></i>	<i><any></i>		Optional;